

Product Data Sheet

5010-XXX Series Vertical Lifelines

The 5010-XXX Series of Vertical lifelines are made from a combination fiber rope with a firm lay, excellent wear and a high strength to weight ratio. Produced with high strength continuous filament polyester surface yarns wrapped over high tenacity Ultra Blue Fiber. All spliced lifelines are supplied with a permanently attached safety rating tag and shrink tube over splice areas. All plain ends are heat sealed and protected with shrink tubing.

Specifications

Diameter - 5/8" (16mm)
Material- Polyester / Ultra Blue Polypropylene
Construction - 3 Strand Firm Lay
Strength - 7500lbs Minimum
Elongation - Less than 22% at 1800lbs
End Finish - 5 Tuck splice with Thimble Eye (Except on 5010-600' Roll)
Hardware - 3062 Carabiner (Except on 5010-600' Roll)
Identity Tracer - Green/Red
Compliance - ANSI Z359.1-1992, OSHA 1926



| Part # | Length |
|----------|-----------|
| 5010-50 | 50' |
| 5010-100 | 100' |
| 5010-150 | 150' |
| 5010-200 | 200' |
| 5010-250 | 250' |
| 5010-300 | 300' |
| 5010-600 | 600' Roll |



Reliance Industries L.L.C.

P.O. Box 2046

Deer Park, TX 77536

Toll Free 888-362-2826 · Fax 281-930-8666

Visit us at www.relsafe.com

RELIANCE
INDUSTRIES