

SKYLOC® 4015/4020 Self Retracting Lifelines



Skyloc™ Self Retracting Lifelines

Self Retracting lifelines are among the best options for both fall arrestor and deceleration devices. Skyloc™ self retracting lifelines are designed to arrest a fall in 2' (.6m) or less and limit the maximum arresting force (MAF) to 900 lbs (4 kN) Deceleration distance will not exceed 42" (1.1m). With short fall arrest distances and lower MAF's the Skyloc™ is the best option where fall clearance is a concern.

Product Features

- Lightweight thermoplastic case
- Two fast and positive cam-driven locking pawls.
- Available with cable or polyester web
- Forged steel Pelican hook
- Capacity: 1 worker, 310 lbs (140.6kg) max. weight (worker + tools)

Available Models

Part #	Length	Weight	Case	Line	Hook
4015	18' (5.4m)	7.5 (3.4 kg)	Thermoplastic	3/16" (4.5mm) Galvanized Cable	3006
4020	20' (6.1m)	6.8 (3 kg)	Thermoplastic	1" (25mm) Polyester Web	3006

Warnings

Read user manual and labels before use. Failure to observe instructions could result in injury or death. Inspect SRL before each use. If this product has been subjected to a fall arrest load, return to an authorized service center for recertification. This retractable requires a minimum activation speed. Do not use where sliding motion would not reach activation speed. Do not install or use near electrical hazards or energized equipment. Reduce swing fall hazards by keeping workers directly beneath device. Always inspect attachment of snap to be sure it cannot load snap gate in a manner that could create an accidental disengagement. Never allow the SRL to retract uncontrollably; use a tag line to allow slow retraction of line into the housing. Do not allow the wire rope to come into contact with sharp surfaces that could damage the cable. Do not climb above your anchorage point.

