

Polyurethane Coated Full Body Harnesses & Shock Absorbing Lanyards

These products have been specifically designed for use in harsh work environments. With a .05” Polyurethane coating encapsulating the web, these products are easier to clean and more resilient to cuts and burns in harsh work environments than our standard, uncoated products.



800005

800055

802005



731456

741426



741256

*761426

Product Features - Harnesses

- .05” Polyurethane coating on webbing increases durability and eases cleaning
- Tattletale™ webbing has an interior ply of contrasting bright red “strength” yarns that increase webbing strength to 7000 lbs (31kN) and instantly reveal cuts or abrasion
- Built-in impact load indicators
- Bar-coded individual serial numbers for traceability
- Indelible serial number in back plaque
- “Floating” thigh stitching reduces binding
- Improved geometry brings buckles to front of thigh
- Angled stitching for “tailored” sub-pelvic fit
- Extra large back pad eliminates dangerous ‘D-ring droop’
- No elastic webbing
- Heat-set labels won’t come off
- Corrosion resistant grommets
- Extra thick woven (not sewn) seat webbing for added durability

Available Models - Harnesses

Part #	Description
800005	Dorsal D-ring, Tongue Buckle legs
800055	Dorsal D-ring, Pass-Thru legs
802005	Dorsal & Positioning D-rings, Tongue Buckle legs

Product Features - Lanyards

- .05” Polyurethane coating on webbing increases durability and eases cleaning
- Designed to withstand exposure to the harshest of work environments
- Limits arresting forces to less than 900 lbs (4kN) in a 6’ (1.8m) free fall (*761426 BigBoy™ limits forces to 1800 lbs (8kN) in same distance)
- Lanyard elongation will not exceed 42” (1.07m) in a 6’ (1.8m) free fall arrest
- Clear Shrink tubing for shock pack and label inspectability
- Serialized and barcoded for traceability
- All hooks comply with the stringent ANSI Z359.1-2007

Available Models - Lanyards

Part #	Description
731456	Single leg, 1 Pelican, 1 Steelhead™ Tie-back hook
741426	Dual leg, 1 Pelican, 2 Steelhead™ Tie-back hooks
741256	Dual leg, 1 Pelican, 2 Rebar hooks
761426	BigBoy™ Dual leg, 1 Pelican, 2 Steelhead™ Tie-back hooks

*Steelhead™ Tie-Back hooks can be used to tie the lanyard back on to itself when necessary. Only approved anchorage points may be used.

