Roto-Loc TM Coverhead Self Retracting Lanyard





Roto-Loc™ Overhead Self Retracting Lanyard

The Roto-Loc™ Overhead Self Retracting Lanyard is specifically designed for use in overhead mounting applications that require the durability of wire rope but in a smaller package and lower price, than the typical cable unit. The Roto-Loc™ Overhead is ideal for use in long term applications such as order pickers and forklifts or in general industry overhead maintenance. It features an all alloy steel frame and cam activated Failsafe™ locking mechanism, giving you confidence in short extensions without nuisance lock-ups.

Roto-Loc™ Overhead Features:

- Internal rotary braking mechanism.
 - ✓ Fast acting, smooth braking that keep forces low without excessive extension.
- High strength alloy steel frame and locking mechanism.
 - ✓ Surpasses OSHA and ANSI requirements for strength.
- Fast acting, cam driven Failsafe™ locking mechanism.
 - ✓ Ensures fast, consistent locking, arresting the fall within inches without the nuisance lock-ups of centrifugal locking mechanisms.
- Rugged ABS housing with a Santoprene overmold.
 - ✓ Designed to endure the rigors of daily use in tough environments.
 - Recessed labels, to last the life of the product.

Roto-Loc™ Overhead Specifications:

Lifeline: 3/16" 7x19 Galvanized Wire Rope

Frame: High Strength Alloy Steel

Swivel: High Strength Alloy Steel

Main Spring: Grade 301 Stainless Steel

Housing: ABS Thermoplastic with Santoprene™ Overmold

Housing Dimensions: 5.2"x3.3"x6.1"

Performance Specifications:

Meets ANSI Z359.14 Class A

Arrest Distance: 24" or less

Average Arrest Force: 1,350 lbs. or less

Max Arrest Force: 1,800 lbs. or less

Maximum Working Capacity:

400 lbs. (Including tools and equipment)

Roto-Loc™ Overhead Part Numbers

Part #	Working Length	Weight	Configuration	Hook Type
4400009-1	9' 2.7m	5.2 lb. 2.3 kg	Overhead Mount	3007 Pelican Swivel Snap Hook
4400012-1	12' 3.6m	5.4 lb. 2.4 kg	Overhead Mount	3007 Pelican Swivel Snap Hook

This brochure contains only a general description of the products shown, it is not to be construed, in any manner, as a replacement for the product instructions. Under no circumstances shall the products be used by untrained or unqualified individuals and not until the product instructions and labels provided have been thoroughly read, understood and followed. Failure to follow instructions could result in serious injury or death. Santoprene is a trademark of the Exxon Mobile Corporation.

RELIANCE fall goodes jidn

